

IN THE CLAIMS

1. (Original) A method of forming multi-layers for manufacturing a thin film transistor (TFT) using multiple process chambers, comprising:
forming a first layer on a transparent substrate using a first physical vapor deposition in a first process chamber;
transferring the substrate including the first layer to a second process chamber without breaking vacuum; and
sequentially forming a second layer in the second process chamber using a second physical vapor deposition on the first layer ~~without breaking vacuum~~.
2. (Original) The method of claim 1, wherein the physical vapor deposition for forming the first layer comprises pulsed-DC or RF sputtering.
3. (Original) The method of claim 1, wherein the first layer is silicon dioxide.
4. (Original) The method of claim 3, wherein the second layer is amorphous silicon.
5. (Currently Amended) The method of claim 1, wherein said forming a first layer is performed by sputtering using a first target comprising a silicon material selected from the group consisting of polysilicon and single-crystal silicon ~~having a predetermined resistivity~~.
6. (Currently Amended) The method of claim 5, wherein the first layer is silicon dioxide and is sputter deposited from the first target with ~~an oxygen reactive gas~~.
7. (Original) The method of claim 5, wherein the first layer is silicon dioxide and is sputter deposited from the first target with a reactive gas mixture comprising oxygen and He.
8. (Original) The method of claim 5, wherein the first layer is silicon dioxide and is sputter deposited from the first target with a reactive gas mixture comprising oxygen and H₂.
9. (Original) The method of claim 5, wherein the first layer is silicon dioxide and is sputter deposited from the first target with a reactive gas mixture comprising oxygen, He, and H₂.

10. (Original) The method of claim 5, wherein the first layer is silicon dioxide and is sputter deposited from the first target with a reactive gas mixture comprising oxygen and any one of Ar, Ne, or Kr.

11. (Original) The method of claim 5, wherein the first layer is silicon dioxide and is sputter deposited from the first target with a reactive gas mixture comprising oxygen, He, and any one of Ar, Ne, or Kr.

12. (Original) The method of claim 11, wherein the reactive gas mixture comprises oxygen, He and Ar, and wherein a ratio of Ar in He is between approximately 3-20% Ar in Helium.

13. (Currently Amended) The method of claim 5, wherein the predetermined ~~resistivity~~ resistivity R1 is in a range of approximately 1-50 Ohm-cm.

14. (Original) The method of claim 1, wherein said forming a first layer is performed by sputtering using a first target comprising silicon dioxide.

15. (Original) The method of claim 1, wherein said forming a second layer is performed by sputtering using a target formed of a material selected from the group consisting of single crystalline silicon and polycrystalline silicon.

16. (Original) The method of claim 1, wherein the physical vapor deposition for forming the second layer comprises regular-DC, pulsed DC or RF sputtering.

17. (Withdrawn) A thin film transistor, comprising:
a transparent substrate;
a first layer formed on the substrate using a first physical vapor deposition; and
a second layer formed sequentially on the first layer using a second physical vapor deposition, without breaking vacuum.

18. (Withdrawn) The thin film transistor of claim 17, wherein the first layer is formed using pulsed-DC or RF sputtering.

19. (Withdrawn) The thin film transistor of claim 17, wherein the first layer is silicon dioxide.

20. (Withdrawn) The thin film transistor of claim 19, wherein the second layer is amorphous silicon.

21. (Withdrawn) A poly-Si thin film transistor, comprising:
a transparent substrate;
a first layer formed on the substrate using a physical vapor deposition; and
a second layer formed sequentially on the first layer, using the physical vapor deposition and an annealing process for crystallization, without breaking vacuum.

22. (Withdrawn) The thin film transistor of claim 21, wherein the physical vapor deposition for forming the first layer comprises pulsed-DC or RF sputtering.

23. (Withdrawn) The thin film transistor of claim 21, wherein the first layer is silicon dioxide.

24. (Withdrawn) The thin film transistor of claim 23, wherein the second layer is polycrystalline silicon.

25. (Withdrawn) A display device, comprising:
a transparent substrate;
a first layer formed on the substrate using a first physical vapor deposition; and
a second layer formed sequentially on the first layer using a second physical vapor deposition, without breaking vacuum.

26. (Withdrawn) The device of claim 25, wherein the first layer is formed using pulsed-DC or RF sputtering.

27. (Withdrawn) The device of claim 25, wherein the first layer is silicon dioxide.

28. (Withdrawn) The device of claim 27, wherein the second layer is amorphous silicon.

29. (New) The method of claim 1, wherein no annealing is performed between forming a first layer and forming a second layer.